

PRODUCT DESCRIPTION

• Yellow laminate Coverall

FEATURES

- Higher barrier
- Pass EN13034 liquid splash Type 6
- Pass EN ISO 13982-1 particulates Type 5
- Pass EN 14605 liquid spray Type 4
- Passed penetration for ASTM F-903 Recommended List of Chemical
- Anti-stat EN1149

APPLICATIONS

- Chemical handling
- Manufacturing, environmental clean up
- Pressure washing
- Particle handling

chemical penetration testing result as ASTM F-505			
Challenge Chemical	CAS Number	Physical State	Result
Acetone	67-64-1	Liquid	Passed
Acetonitrile	75-05-8	Liquid	Passed
Ammonia Gas	7664-41-7	Gas	Passed
1,3-Butadiene Gas	106-99-0	Gas	Passed
Carbon Disulfide	75-15-0	Liquid	Passed
Chlorine Gas	7782-50-5	Gas	Passed
Dichloromethane	75-09-2	Liquid	Passed
Diethylamine	109-89-7	Liquid	Passed
Dimethyl Formamide	68-12-2	Gas	Passed
Ethyl Acetate	141-78-6	Liquid	Passed
Ethylene Oxide Gas	75-21-8	Gas	Passed
n-Hexane	110-54-3	Liquid	Passed
Hydrogen Chloride Gas	7647-01-0	Gas	Passed
Methanol	67-56-1	Liquid	Passed
Methyl Chloride Gas	74-87-3	Gas	Passed
Nitrobenzene	98-95-3	Liquid	Passed
Sodium Hydroxide, 50%	1310-73-2	Liquid	Passed
Sulfuric Acid, 98%	7664-93-9	Liquid	Passed
Tetrachloroethylene	127-18-4	Liquid	Passed
Tetrahydrofuran	109-99-9	Liquid	Passed
Toluene	108-88-3	Liquid	Passed

Chemical penetration testing result as ASTM F-903



Testing is performed on fabric samples only, not finished garments

DISCLAIMER: The information supplied in this document is for guidance only and should not be construed as a warranty. All implied warranties are expressly disclaimed, including without limitation any warranty of merchantability and fitness for use. All users of the material are responsible for assuring that it is suitable for their needs, environment and end use. All data is subject to change as Berry Global deems appropriate. Refer to http://www.berryglobal.com/ for contact information.