

CHAIN & DRIVE SPRAY

Page: 1 Revision date: 05/02/2016

Revision No: 12

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: CHAIN & DRIVE SPRAY

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Chain Lubricant.

1.3. Details of the supplier of the safety data sheet

Company name: ROCOL

	ROCOL House			
	Swillington			
	Leeds			
	West Yorkshire			
	LS26 8BS			
	ENGLAND			
Tel:	+44 (0) 113 232 2700			
Fax:	+44 (0) 113 232 2740			
Email:	customer-service@rocol.com			

1.4. Emergency telephone number

Emergency tel: +44 (0) 113 232 2600

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: STOT SE 3: H336; Aquatic Chronic 3: H412; Flam. Aerosol 2: H223; -: H229

Most important adverse effects: Flammable aerosol. Pressurised container: May burst if heated. May cause drowsiness or dizziness. Harmful to aquatic life with long lasting effects.

2.2. Label elements

Label elements:

Hazard statements:	H223: Flammable aerosol.
	H229: Pressurised container: May burst if heated
	H336: May cause drowsiness or dizziness.
	H412: Harmful to aquatic life with long lasting effects.
Hazard pictograms:	GHS02: Flame
	GHS07: Exclamation mark



CHAIN & DRIVE SPRAY

	Page	e: 2	2
Signal words:	Warning		
Precautionary statements:	P410+412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C.		
	P251: Do not pierce or burn, even after use.		
	P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.		
	No smoking.		
	P285: In case of inadequate ventilation wear respiratory protection.		
	P261: Avoid breathing dust/fumes/gas/mist/vapours/spray.		
	P211: Do not spray on an open flame or other ignition source.		
	P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.		
	P312: Call a POISON CENTER/doctor if you feel unwell.		
			1

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS - REACH registered number(s): 01-2119463258-33-XXXX

EINECS	CAS	PBT / WEL	CLP Classification	Percent
919-857-5	-	-	Flam. Liq. 3: H226; Asp. Tox. 1: H304;	20-50%
			STOT SE 3: H336; -: EUH066	

HYDROTREATED MINERAL OIL (LESS THAN 3% DMSO EXTRACT)

265-155-0	64742-52-5	Substance with a Community	-	20-50%
		workplace exposure limit.		

HYDROTREATED LIGHT DISTILLATE (PETROLEUM)

265-149-8	64742-47-8	-	Flam. Liq. 3: H226; Skin Irrit. 2: H315;	2.4-10%
			STOT SE 3: H335; Asp. Tox. 1: H304;	
		Aquatic Chronic 2: H411; STOT SE 3:		
			H336	

CARBON DIOXIDE AEROSOL PROPELLANT

204-696-9	124-38-9	Substance with a Community	Press. Gas: H280	2.4-10%
		workplace exposure limit.		

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

CHAIN & DRIVE SPRAY

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

CHAIN & DRIVE SPRAY

_

-

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS

Workplace exposure limits:		Respirable dust		
State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1200mg/m3, 197ppm	-	-	-

HYDROTREATED MINERAL OIL (LESS THAN 3% DMSO EXTRACT)

5mg/m3

UK	

-

-

CARBON DIOXIDE AEROSOL PROPELLANT

UK 5000ppm 9150mg/m3 15000ppm 27400mg/m3

DNEL/PNEC Values

Hazardous ingredients:

HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS

Туре	Exposure	Value	Population	Effect
DNEL	Dermal (repeated dose)	300	Workers	Local
DNEL	Inhalation (repeated dose)	1500	Workers	Systemic
DNEL	Dermal	300	Consumers	Systemic
DNEL	Inhalation (repeated dose)	900	Consumers	Systemic
DNEL	Oral (repeated dose)	300	Consumers	Systemic

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Respiratory protection: Self-contained breathing apparatus must be available in case of emergency. Gas/vapour filter, type A: organic vapours (EN141). Hand protection: Protective gloves. Nitrile gloves. Eye protection: Safety glasses. Ensure eye bath is to hand.

CHAIN & DRIVE SPRAY

Page: 5

Skin protection: Protective clothing.

Environmental: No data available

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State:	Aerosol		
Colour:	Yellow		
Odour:	Characteristic odour		
Evaporation rate:	Fast		
Oxidising:	Non-oxidising (by EC criteria)		
Solubility in water:	Not miscible		
Viscosity:	Oily		
Boiling point/range°C:	>35 M	lelting point/range°C:	<-50
Flammability limits %: lower:	No data available.	upper:	No data available.
Flash point°C:	40 Part.co	oeff. n-octanol/water:	No data available.
Autoflammability°C:	>200	Vapour pressure:	No data available.
Relative density:	<1	pH:	Approx. 7
VOC g/l:	355		

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

CHAIN & DRIVE SPRAY

Page: 6

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS

DERMAL	RBT	LD50	> 5000	ppmV
DUST/MIST	RAT	4H LC50	>5	mg/l
ORAL	RAT	LD50	> 5000	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
STOT-single exposure	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS

ALGAE	-	>1000	mg/l
Daphnia magna	-	>1000	mg/l
GREEN ALGA (Selenastrum capricornutum)	-	100	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H LC50	>1000	mg/l

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

CHAIN & DRIVE SPRAY

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations:	Transfer to a suitable container and arrange for collection by specialised disposal company.
Recovery operations:	No data available
Waste code number:	16 05 05
Disposal of packaging:	Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.
NB:	The user's attention is drawn to the possible existence of regional or national regulations
	regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1950

14.2. UN proper shipping name

Shipping name: AEROSOLS, FLAMMABLE

14.3. Transport hazard class(es)

Transport class: 2.1

14.4. Packing group

Packing group: n/a

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk: No data available.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: No data available

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

CHAIN & DRIVE SPRAY

Section 16: Other information				
Other information				
Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EC) No 1272/2008.			
	This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.			
	······			
	Product label must specify: HYDROTREATED LIGHT DISTILLATE (PETROLEUM) (CAS 64747-47-8)			
Dhreece used in a 2 and a 2.				
Phrases used in S.2 and S.3:	EUH066: Repeated exposure may cause skin dryness or cracking. H223: Flammable aerosol.			
	H226: Flammable liquid and vapour.			
	H229: Pressurised container: May burst if heated			
	H280: Contains gas under pressure; may explode if heated.			
	H304: May be fatal if swallowed and enters airways.			
	H315: Causes skin irritation.			
	H335: May cause respiratory irritation.			
	H336: May cause drowsiness or dizziness.			
	H411: Toxic to aquatic life with long lasting effects.			
	H412: Harmful to aquatic life with long lasting effects.			
Legal disclaimer:	The above information is believed to be correct but does not purport to be all inclusive and			
	shall be used only as a guide. This company shall not be held liable for any damage resulting			
	from handling or from contact with the above product.			