732+

File Number: E251343





## **COMPANY**

Dow Silicones (Shanghai) Co Ltd SONGJIANG INDUSTRIAL ZONE 448 E RONGLE RD SHANGHAI, 201613 China

**FLAMMABILITY PROPERTIES** 

## **MODEL INFO**

## 732+

Silicone "Room Temperature Vulcanizing" (RTV), furnished as one liquid component + – Except a 150 C Mechanical w/o impact RTI where elongation is not essential.

Flammability	НВ	ANSI/UL 94
(1.9 mm, Color: ALL)		
SO/IEC FLAMMABILITY PROPERTIES	VALUE	TEST METHOD
Flammability	HB75	IEC 60695-11-10
(1.9 mm, Color: ALL)		
THERMAL PROPERTIES	VALUE	TEST METHOD
Relative Thermal Index - Electrical Strength (1.9 mm)	140 °C	UL 746B
	140 °C	UL 746B

**VALUE** 

Report Date: 1971-02-22 Revision Date: 2022-05-30

**TEST METHOD** 

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2022 UL LLC"