Safety Data Sheet

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II - Germany



1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Identification of the substance/preparation

Product name or Trade name:

Sikaflex®-291i

Use of the substance/preparation: Chemical product for construction and industry

Company/undertaking identification

Manufacturer/Distributor : SSC AG

Street/postbox : Industriestrasse
Town/City and Post Code : 6060 Sarnen
Country : Switzerland
Telephone no. : +41416669966
Fax no. : +41416669660
e-mail address of person : EHS@de.sika.com

responsible for this SDS

Emergency telephone number

: +49-(0)173-6774799 (Only out of office hour)

2. HAZARDS IDENTIFICATION

The product is not classified as dangerous according to Directive 1999/45/EC and its amendments.

Additional warning phrases

: Contains isocyanates. See information supplied by the manufacturer. Contains Sika Hardener LH (1,6-Hexanedialdimine), Pentamethyl piperidylsebacate. May produce an allergic reaction.

See section 11 for more detailed information on health effects and symptoms.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical family/ : Filled reactive PUR-polymer

Characteristics

4. FIRST AID MEASURES

First-aid measures

Inhalation : Get medical attention if symptoms occur.

Ingestion: Do not induce vomiting unless directed to do so by medical personnel. Maintain an

open airway. Seek immediate medical attention.

Skin contact: Flush contaminated skin with plenty of water. Remove contaminated clothing and

shoes. Get medical attention if symptoms occur.

Eye contact: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower

eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10

minutes. Get medical attention.

Notes to physician : No specific treatment. Treat symptomatically. Contact poison treatment specialist

immediately if large quantities have been ingested or inhaled.

See section 11 for more detailed information on health effects and symptoms.

Date of issue : 07.10.2010. MSDS no. : 131725 1/5

Sikaflex®-291i 07.10.2010 2/5

5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable

: Use an extinguishing agent suitable for the surrounding fire.

Not suitable

Special exposure hazards

: In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous combustion

products

: Decomposition products may include the following materials:

carbon dioxide carbon monoxide

halogenated compounds

metal oxide/oxides

Special protective equipment for fire-fighters Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

ACCIDENTAL RELEASE MEASURES 6.

Personal precautions

: Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment (see section

Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Large spill

Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with noncombustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13).

Small spill

Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container.

7. HANDLING AND STORAGE

Handling

: Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Avoid contact with eyes, skin and clothing. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use.

Storage

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

Packaging materials

Recommended : Use original container.

EXPOSURE CONTROLS/PERSONAL PROTECTION 8.

Exposure limit values

MSDS no. : 131725 : 07.10.2010. Date of issue 2/5 Sikaflex®-291i 07.10.2010 3/5

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredient name

Occupational exposure limits

No exposure limit value known.

Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to European Standard EN 689 for methods for the assessment of exposure by inhalation to chemical agents and national guidance documents for methods for the determination of hazardous substances.

Exposure controls

Occupational exposure

controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants. If this product contains ingredients with exposure limits, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing.

Respiratory protection

No special measures required.

Hand protection

: hemical-resistant, impervious gloves complying with an approved standard should be orn at all times when handling chemical products if a risk assessment indicates this is necessary. Reference number EN 374. Recommended: Butyl rubber/nitrile

rubber gloves.

Eye protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.

Skin protection

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: Use barrier skin cream.

Environmental exposure controls

Controis

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

9. PHYSICAL AND CHEMICAL PROPERTIES

General information

Appearance

Form : Paste.
Colour : Various.
Odour : Faint odour.

Important health, safety and environmental information

 Flash point
 : Closed cup: >150 °C (>302 °F)

 Density
 : ~1.34 g/cm³ [20 °C (68 °F)]

Solubility: Insoluble in the following materials: water

Date of issue : 07.10.2010. MSDS no. : 131725 3/5

Sikaflex®-291i 07.10.2010 4/5

10. STABILITY AND REACTIVITY

Stability : The product is stable.

Conditions to avoid : No specific data.

Materials to avoid : No specific data.

Hazardous decomposition

products

: Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

11. TOXICOLOGICAL INFORMATION

Potential acute health effects

Inhalation: May cause irritation.

Ingestion: Can cause gastrointestinal disturbances.

Skin contactEye contactMay cause skin irritation.May cause eye irritation.

Chronic effects: No known significant effects or critical hazards.

12. ECOLOGICAL INFORMATION

Environmental effects

: Avoid contact of spilt material and runoff with soil and surface waterways. Do not empty into drains; dispose of this material and its container in a safe way.

13. DISPOSAL CONSIDERATIONS

Methods of disposal : Completely emptied packagings can be given for recycling. Packaging containing

remains of dangerous substances, as well as packagings disposed of remains can be

unharmed eliminated in accordance with the regulations.

Packaging : ompletely emptied packagings may be given for recycling. Empty packaging may still

contain hazardous residues. Empty packaging should be removed by a licensed

waste contractor.

Sika has agreed disposal contracts for all packaging which is brought into circulation

in Germany.

15 01 10* packaging containing residues of or contaminated by dangerous

substances

For further details see www.sika.de

14. TRANSPORT INFORMATION

International transport regulations

ADR

Not regulated.

IMDG

Not regulated.

Marine pollutant : No

IATA

Not regulated.

Date of issue : 07.10.2010. MSDS no. : 131725 4/5

Sikaflex®-291i 07.10.2010 5/5

15. REGULATORY INFORMATION

EU regulations

Classification and labeling have been determined according to EU Directives 67/548/EEC and 1999/45/EC (including amendments) and take into account the intended product use.

Additional warning phrases : Contains isocyanates. See information supplied by the manufacturer. Contains Sika

Hardener LH (1,6-Hexanedialdimine), Pentamethyl piperidylsebacate. May produce

an allergic reaction.

VOC content (EU) : VOC (w/w): 0%

National regulations

Hazard class for water 1 according Appendix No. (Gemäß VwVws vom 17. Mai 1999)

4

16. OTHER INFORMATION

History

Date of printing : 02.11.2010 **Date of issue** : **07.10.2010**.

Date of previous issue : No previous validation.

Indicates information that has changed from previously issued version.

Notice to reader

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Date of issue : 07.10.2010. MSDS no. : 131725 5/5